



MT28-3VI ☑

${\bf Reciprocating\ compressor,\ MT28JE3MVE}$

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

I NODOCI DE INIES	
Gross weight	24.88 Kg
Net weight	23 Kg
Volume	37.73 Liter
EAN	5702428839785
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	MT028-3
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	3/8 in
Discharge connection size [in]	1 in
Drawing number	8501024e
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MT
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 ℃
High Side TS Min	-35 °C



PRODUCT DETAILS	
High Side Volume	0.3 L
High value of nominal voltage at	230 V
60Hz [V]	230 (
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 ℃
Low Side Volume	7.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	57 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	18.4 bar
MCC	16 A
Model number	MT28JE3MVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	385 mm
Packaging length [mm]	330 mm
Packaging weight [Kg]	26 kg
Packaging width [mm]	295 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	MT
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R22
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	5a332c1b-1d1b-4998-8115-
	d0929877ecb4
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves,
	rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts,
	nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm



PRODUCT	DETAILS
---------	---------

Suction connection material	-
Suction connection pipe size [in]	1/2 in
Suction connection size [in]	1 in
Swept volume [cm3]	48.06 cm ³
Technology	Reciprocating
Test Dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	333 mm
Туре	MT028
UK RoHS compliance	Out of scope
Viscosity [cP]	32 cP
Winding resistance for three-	1.41 Ohm
phase compressors with identical	
windings [Ohm]	
Proposition 65	WARNING: Cancer and Reproductive
	Harm
	www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



120Z0760 🗷

Mounting, Compressor kitMounting kit 1 cylinder low



8156130 🗷

Connector, GASKET

Gasket, 1"



8156134 🗷

Electrical component, Terminal box

Service kit for terminal box $80\,x\,96$ mm, including 1 cover, 1 clamp



8153010 🗷

Connector, Solder Sleeve

Solder sleeve, P01 (1" rotolock, 3/8" ODF)



8153007 🗷

Connector, Solder Sleeve

Solder sleeve, P06 (1" rotolock, 1/2" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories



8156009 🗷

Connector, GASKET

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



120Z0575 🗷

Acoustic hood, Reciprocating

Acoustic hood for one-cylinder compressor

Spare Parts



7703004 🗷

Connector, Valve set

Valve set, V06 (1"~1/2"), V01 (1"~3/8")



7773106 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 54 W, 230 V, CE mark, UL



8156145 🗷

Connector, GASKET

Gasket for oil sight glass (black chloroprene)



7754001 🗷

Lubricant, 160P

Mineral oil, 160P, 2-litre can



8168031 🗷

Connector, Rotolock service valve

Rotolock valve, V06 (1" rotolock, 1/2" ODF)



8168027 🗷

Connector, Rotolock service valve

Rotolock valve, V01 (1" rotolock, 3/8" ODF)



8156019 🗷

Connector, Sight glass

Oil sight glass with gaskets (black and white)

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



120Z0459 🗷

Crankcase heater, PTC heater

PTC heater 27W, CE mark, UL