



120F0280 🗠

Reciprocating compressor, NTZ068A3LR1B

Refrigerants: R404A; R452A; R454C; R454A; R455A, Segment usage: Refrigeration LT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	24.75 Kg
Net weight	23 Kg
Volume	37.73 Liter
EAN	5702428665322
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	NTZ068-3B
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501026f
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-1, 7(a), 7(c)-1, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	NTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 ℃

Product Detail | Reciprocating compressor, NTZ068A3LR1B

PRODUCT DETAILS	
High Side Volume	0.3 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	7.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	48.5 A
Max pressure (PS) - high side	28.5 bar
Max pressure (PS) - low side	22.6 bar
Max pressure (F3) - Iow side	14.8 A
Model number	NTZ068A3LR1B
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	370 mm
Packaging length [mm]	385 mm
Packaging width [mm]	285 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	NTZ
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R404A
Refrigerants	R452A
	R454C
	R454A
	R455A
Rotational speed at 60Hz [rpm]	3500 rpm
Segment usage	Refrigeration LT
Shipped fittings	Suction and discharge solder sleeves,
	rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts,
	nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm



PRODUCT DETAILS

Suction connection material	-	
Suction connection pipe size [in]	5/8 in	
Suction connection size [in]	1 1/4 in	
Swept volume [cm3]	68 cm ³	
Technology	Reciprocating	
Test Dif [bar] [Max]	30 bar	
Test HP [bar] [Max]	30 bar	
Test LP [bar] [Max]	25 bar	
Torque earth [Nm]	3 N-m	
Torque power [Nm]	3 N-m	
Total height [mm]	333 mm	
Туре	NTZ068	
UK RoHS compliance	Out of scope	
Viscosity [cP]	32 cP	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories 8156009 **Connector, GASKET** Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white 8153011 🕑 **Connector, Solder Sleeve** Solder sleeve, P09 (1-1/4" rotolock, 5/8" ODF) 7750009 🕑 Electrical component, Discharge thermostat kit Discharge thermostat kit 8156130 Connector, GASKET Gasket, 1" 8156134 🗠 Electrical component, Terminal box Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp 8153007 **Connector, Solder Sleeve** Solder sleeve, P06 (1" rotolock, 1/2" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗷

Product Detail | Reciprocating compressor, NTZ068A3LR1B





Accessories



8156131 🛛

Connector, GASKET Gasket, 1-1/4"



8156001 🖻 Mounting, Compressor kit

Mounting kit for one and two-cylinder compressor, including 3 grommets, 3 bolts



120Z0575 🖄

Acoustic hood, Reciprocating Acoustic hood for one-cylinder compressor

Spare Parts

	120Z0459 Crankcase heater, PTC heater PTC heater 27W, CE mark, UL
	8156145 🖻 Connector, GASKET Gasket for oil sight glass (black chloroprene)
Ç	7773106 C Crankcase heater, Belt heater Belt type crankcase heater, 54 W, 230 V, CE mark, UL
	120Z0638 ☑ Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can
The second se	8168031 C Connector, Rotolock service valve Rotolock valve, V06 (1" rotolock, 1/2" ODF)
The second se	8168033 ☑ Connector, Rotolock service valve Rotolock valve, V09 (1-1/4" rotolock, 5/8" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Product Detail | Reciprocating compressor, NTZ068A3LR1B

ENGINEERING TOMORROW



Spare Parts



7703005 🖻

Connector, Valve set Valve set, V09 (1-1/4"~5/8"), V06 (1"~1/2")



8156019 C Connector, Sight glass Oil sight glass with gaskets (black and white)

For more information, please use this link to visit the product page on Danfoss Product Store 🗈