

Electronic Refrigerant Scale



ChargeTron®

FOR U.S. JOBS
UNIWELD EMPLOYS OVER 300 WORKERS

Now you can accurately weigh and transfer refrigerant to and from the A/C system. You will be working with a compact, battery powered, portable (7.2 lbs) workstation that has the cast aluminum scale built right into its high impact plastic carrying case. The optional charging module plugs into the scale to automatically transfer a preset amount of refrigerant.

LCD DISPLAYS
POUNDS/OUNCES OR
KILOGRAMS/GRAMS

OPTIONAL CHARGING MODULE



PART #53651 HAS
ADDITIONAL 120V AC
POWER OUTLET



53650

5 HVAC/R TOOLS

Tare Weight:	Zeros out scale at any time.
Power:	9 Volt Alkaline Battery. Auto power off: after 15 minutes of operation without any change in weight, scale turns off. Approximately 48 hours battery life. Optional A/C Power Adaptor.
Two Weight Capacities:	110 lbs. [50 Kg] or 176 lbs. [80 Kg]
Accuracy:	At 110 lbs./50 Kg Capacity: $\pm .2$ oz./10g • At 176 lbs./80 Kg Capacity: $\pm .5$ oz./20g
Weight:	7.2 lbs. [3.26 Kg]
Dimensions:	15" X 13" X 3 3/8" [38cm x 28cm x 8.5cm]
Operating Temperature:	32 °F to 120 °F [0 °C to 50 °C]
Case:	Rugged Plastic Carrying Case with a built-in handle.
Platform Size:	9" X 9" [23cm x 23cm] Ribbed Rubber Mat.
Optional Accessories:	<p>Part# 53651 Automatic Charging Module. Compatible with all refrigerants including R-410A. Maximum working pressure: 300 psi.</p> <p>Part# 53654 Automatic Charging Module. 220V model [no additional power outlet] Compatible with all refrigerants, including R-410A. Maximum working pressure: 300 psi</p> <p>Part# 53652 120V AC Power Adapter connects to ChargeTron® Refrigerant Scale.</p>

50



Uniweld Products, Inc. Fort Lauderdale, FL 33312 U.S.A. Customer Service: 800.323.2111
info@uniweld.com • www.uniweld.com